



Sample image

KG41

Type Size: S0

Classification Contact: Rigid contact bridge

Classification Contact Mat: Silver

Classification Terminal: Screw terminal

IEC 60947-3 EN 60947-3, VDE 0660 Teil 107

Rated insulation voltage U_i

| Voltage (V) | AC / DC |
|-------------|---------|
| 690 | AC |

Rated impulse withstand voltage U_{imp}

| Voltage (kV) | Overvoltage category | Pollution degree | Supply system | Function |
|--------------|----------------------|------------------|--|------------------------------|
| 6 | III | 3 | Valid for lines with grounded common neutral termination | Switch / Switch disconnecter |

Rated uninterrupted current I_u /I_{th}

| Current (A) | Ambient temperature (°C) | Peak temperature (°C) | additional requirements |
|-------------|--------------------------|-----------------------|--|
| 40 | 50 | 55 | Ambient temperature +50°C during 24 hours with peaks up to +55°C |

Conventional enclosed thermal current I_{the}

| Current (A) | Ambient temperature (°C) | Peak temperature (°C) | Additional requirements | No. of stages (from - to) | Mounting | Mounting size |
|-------------|--------------------------|-----------------------|--|---------------------------|----------|---------------|
| 40 | 35 | 40 | Ambient temperature +35°C during 24 hours with peaks up to +40°C | -- | -- | -- |

Rated operational current I_e

| Utilization category | Voltage (V) | Current (A) |
|----------------------|-------------|-------------|
| AC-32A | 20 - 400 | 40 |
| AC-20A | 690 | 40 |
| AC-21A | 20 - 690 | 40 |
| AC-22A | 220 - 500 | 40 |
| AC-22A | 660 - 690 | 40 |

Rated operational power

| Utilization category | Voltage (V) | No. of phases | No. of poles | Power (kW) |
|----------------------|-------------|---------------|--------------|------------|
| AC-3 | 220 - 240 | 3 | 3 | 7,50 |
| AC-3 | 380 - 440 | 3 | 3 | 11 |
| AC-3 | 500 - 500 | 3 | 3 | 15 |
| AC-3 | 660 - 690 | 3 | 3 | 11 |
| AC-23A | 220 - 240 | 3 | 3 | 7,50 |
| AC-23A | 380 - 440 | 3 | 3 | 15 |
| AC-23A | 500 - 500 | 3 | 3 | 18,50 |
| AC-23A | 660 - 690 | 3 | 3 | 15 |

Max Fuse Rating IEC

| Fuse characteristic | No. of Fuses | Current (A) |
|---------------------|--------------|-------------|
| gG | 1 | 50 |

UL60947-4-1, UL508

Rated insulation voltage U_i

| Voltage (V) | AC / DC |
|-------------|---------|
| 600 | AC |

Rated thermal current

| Current (A) | Ambient temperature (°C) | Additional Text |
|-------------|--------------------------|-----------------|
| 42 | 0 - 40 | -- |

General Information
Text

- When intended for use as switch used in Photovoltaic applications the devices shall be provided with a method of being locked in the OFF-position.
- The operating handle and position indicating means to be used with these manual motor controllers should be provided from the manufacturer, or the operating handle and position indicating means to be used should have been previously evaluated in combination with the manual motor controllers.
- When intended for use as a motor disconnecter the device shall be provided with a method of being locked in the OFF-position.

CSA

Rated insulation voltage U_i

| Voltage (V) | AC / DC |
|-------------|---------|
| 600 | AC |

| Rated thermal current | | | |
|-----------------------|-------------|--------------------------|-----------------|
| | Current (A) | Ambient temperature (°C) | Additional Text |
| | 40 | 0 - 40 | - |

GENERAL TECHNICAL INFORMATION

| Tightening torque of screws | |
|-----------------------------|------------------------|
| | tightening torque (Nm) |
| | 1,80 |

| Rated short-time withstand current low | |
|--|----------|
| | Time (s) |
| | 1 |

| Size of conductor | | | | |
|---|-------------------|-------------------------------|---|----------------------|
| composition of conductor | Min. / Max. value | No. of conductor per terminal | Cross section (mm ²) or (AWG/kcmil) | Material of the wire |
| solid wire | Min. | 2 | 0.75mm ² | Copper |
| solid wire | Min. | 1 | 1.5mm ² | Copper |
| flexible wire | Max. | 1 | AWG 6 | Copper |
| flexible wire | Min. | 1 | 2.5mm ² | Copper |
| flexible wire | Max. | 1 | 10mm ² | Copper |
| flexible wire | Min. | 2 | 1.5mm ² | Copper |
| Single-core or stranded wire | Max. | 1 | AWG 6 | Copper |
| Single-core or stranded wire | Max. | 1 | 16mm ² | Copper |
| flexible wire with sleeve | Max. | 1 | 10mm ² | Copper |
| flexible wire with ferrule according to DIN 46228 | Min. | 2 | 0.75mm ² | Copper |
| flexible wire with ferrule according to DIN 46228 | Min. | 1 | 1.5mm ² | Copper |

| Approbations | |
|---------------|---------|
| Specification | Marking |

EAC



CE marking



UK Directives

Lloyd's Register EMEA



IEC 60947-3; EN 60947-3; VDE 0660 Teil107

IEC 60947-3
EN 60947-3

UL 60947-4-1; CSA C22.2 No. 60947-4-1



CSA C.22.2 No.14



GB/T14048.3



Russian Maritime Register of Shipping



| Power loss per pole | |
|---------------------|-----------|
| | Power (W) |
| | 1 |

| Conditions during transport and storing | | |
|---|--------------------------|--|
| Minimum temperature (°C) | Maximum temperature (°C) | additional requirements |
| -40 | 85 | In case of temperatures below -5°C no shock load permissible |

| Shock / Vibration | |
|-------------------------|-------------------------|
| Type of oscillation | Values |
| Resistance to vibration | Min. 4g, 2-100Hz, 1,6mm |
| Resistance to shock | min. 6g, 6ms |

| General Information | |
|---------------------|--|
| Text | |

- EMC Note: This device is suitable for use in environment A and B.

- Do not lubricate or treat contacts.

- Switches may only be mounted, connected and set into operation by qualified persons according to the accepted rules of technology.

General Information*Text*

- Use copper wire only. Do not coat the wire end with tin.
- Terminals with factory fitted jumper links are tightened during production. Take care during installation to ensure factory fitted links are not lost by undoing both sides of linked terminals. After wiring, all terminal screws must be tightened to recommended torque specifications.
- For devices with lockable handles: the position of the handle of these devices shall be marked to guide proper operation.
- The "ON" and "OFF" position may be marked using the symbols "I" and "O" according IEC60417, Symbols 5007 and 5008.

Operating temperature*Min. Temperature [°C]*

-5

Max. Temperature [°C]

55